



Quality Products. Service Excellence.

# 15 Amp Horizontal Rackmount Surge Strip *1583-S Series*

Rear Mounted Receptacles



## Features

- Designed for power distribution from the rear of the unit.
- 1U horizontal 19" rackmount installation.
- With lighted on/off switch or red pilot light to indicate power on.
- 6 outlet models include 2 outlets with extra spacing for clearance of most plug in transformers.
- Available in ASA 61 grey or black powder coat finish.
- [Click here for our non-surge protected version.](#)

## Specification

- Heavy duty 14 gauge wire cord - 14/3 SJT type for extreme temperature ranges and integral molded plug.
- Plug types available are NEMA 5-15P straight blade or NEMA L5-15P locking type.
- Includes 15 Amp, 125 VAC circuit breaker to prevent accidental overload.
- Surge protected panels incorporate our surge module:
  - 18,000 Amp rated MOV's
  - Maximum 54,000 Amps transient current and 780 Joules.
  - 400V Clamp Rating.
  - Protection in all 3 AC modes (L-N, N-G, and L-G).
  - Voltage suppression at the outlet guards against transients from equipment on the outlet strip.
- CSA certified, Standards C22.2 (No. 21-95, No. 42-99 and No. 8-M1986)



## Accessories

- Mounting Hardware
- Rail Depth Adapter Kit

| Black Part No. | ANSI 61 Gray Part No. | Overall Dimensions |       |       | Number of Outlets |      | Outlet    | Cord Length | Plug       | NEMA      | Rack Units |
|----------------|-----------------------|--------------------|-------|-------|-------------------|------|-----------|-------------|------------|-----------|------------|
|                |                       | Height             | Width | Depth | Front             | Rear | NEMA Type |             | Blade Type | Plug Type |            |
| 1583H6A1SBK    | 1583H6A1S             | 1.72               | 19.00 | 2.66  | 0                 | 6    | 5-15R     | 6 ft        | Straight   | 5-15P     | 1U         |
| 1583H6B1SBK    | 1583H6B1S             | 1.72               | 19.00 | 2.66  | 0                 | 6    | 5-15R     | 15 ft       | Straight   | 5-15P     | 1U         |
| 1583H6C1SBK    | 1583H6C1S             | 1.72               | 19.00 | 2.66  | 0                 | 6    | 5-15R     | 6 ft        | Locking    | L5-15P    | 1U         |
| 1583H6D1SBK    | 1583H6D1S             | 1.72               | 19.00 | 2.66  | 0                 | 6    | 5-15R     | 15 ft       | Locking    | L5-15P    | 1U         |
| 1583H8A1SBK    | 1583H8A1S             | 1.72               | 19.00 | 2.66  | 0                 | 8    | 5-15R     | 6 ft        | Straight   | 5-15P     | 1U         |
| 1583H8B1SBK    | -                     | 1.72               | 19.00 | 2.66  | 0                 | 8    | 5-15R     | 15 ft       | Straight   | 5-15P     | 1U         |

Data subject to change without notice

© 2018. Hammond Manufacturing Ltd. All rights reserved.

