



Quality Products. Service Excellence.

Data Center Rack Cabinet *H1 Series*

UL 2416 Rated 3,000 lbs Weight Capacity



The H1 series is designed as your most complete offering for Server, Network and Data Storage applications. This series incorporates Hammond Manufacturing's practical open-design and manufacturing principles with legendary service, support and reliability. H1 cabinets feature an array of enhancements over traditional cabinets, with cooling performance and enhanced security features demanded by today's IT manager.

- Mounting Heights: 42U, 45U, 48U & 52U
- Overall Widths: 24", 30" & 31.5"
- Overall Depths: 42" & 48"
- Paint Finish: Black & White
- Two (2) interchangeable top panels
- Cabinet doors have an attractive curved and ribbed surface for added stability.

Standard Configuration Includes

- 14-Gauge welded steel frame with included leveling feet, recessed casters and grounding studs.
- Two (2) pairs of infinitely adjustable 19" EIA compliant square hole punched rails with rail unit markings.
 - Mounting rails in 30" and 31.5" wide frames, include three (3) 1U accessory mounting slots.
- Front 79% airflow vented front door and split rear (barn) doors.
- One (1) Solid, One (1) Brushed cable entry interchangeable top panels.

Optional Components

- Solid doors and passive air chimney
- Aisle containment
- Bottom panel with brushed gasket
- Side Panels - one (1) set per side
- Finger and ring cable managers
- Chimney/fan top panels

Specifications

- Constructed in 14-gauge steel.
- 48" Depth cabinet includes:
 - Four (4) large cable entry knockouts at the rear top/bottom
 - Two (2) large cable entry knockouts at the front/top
- Grounding studs bonded to frame, side panels and doors.
 - Front and rear studs conform to PET.
- Complies with Seismic IBC 2012 Zone-4 standards when used with **C4K-Z4** Seismic Bolt Down Kit.
 - Structurally adequate to safely resist 1,000 lbs (454 kg) of equipment and self-weight in seismic zone.
- UL Listed 2416 rated for up to 3,000 lbs (1,360 kg) static load rating.
- Rated for up to 2,200 lbs (997.90 kg) rolling caster load rating. Heavy duty casters are also available.



- Finished in textured black or white powder paint.
- TAA Compliant.
- RoHS Compliant.
- Manufactured in North America.

Gallery



Accessories

- Universal Rack Shelf
- Rack Mount Locking Storage Drawer
- Horizontal Lacing Strip
- Horizontal Ring Cable Manager
- Cable Management Arm
- Grounding
- Outlet Strips
- Equipment Cooling
- Adjustable Depth Shelf
- Adjustable Depth Cable Manager
- Horizontal Hinged Cable Manager
- Horizontal Steel Finger Cable Manager
- Mounting Hardware
- Rack Panels
- Caster Set
- Rack and Cabinet Baying/Ganging/Joining Kit

H1 Cabinet Assemblies

Part No. Black	Part No. White	Overall Dimensions			Rack Units	Usable Mounting Dimensions		Optional (Single) Side Panel Part No.	
		Height	Width	Depth		Height	Depth	Black	White
H12442U42BK	H12442U42WH	80.37	24.00	42.00	42	73.50	39.00	H1SP42U42BK	H1SP42U42WH
H13042U42BK	H13042U42WH	80.37	30.00	42.00	42	73.50	39.00	H1SP42U42BK	H1SP42U42WH
H13142U42BK	H13142U42WH	80.37	31.50	42.00	42	73.50	39.00	H1SP42U42BK	H1SP42U42WH
H12442U48BK	H12442U48WH	80.37	24.00	48.00	42	73.50	45.00	H1SP42U48BK	H1SP42U48WH
H13042U48BK	H13042U48WH	80.37	30.00	48.00	42	73.50	45.00	H1SP42U48BK	H1SP42U48WH
H13142U48BK	H13142U48WH	80.37	31.50	48.00	42	73.50	45.00	H1SP42U48BK	H1SP42U48WH
H12445U42BK	H12445U42WH	85.65	24.00	42.00	45	78.75	39.00	H1SP45U42BK	H1SP45U42WH
H13045U42BK	H13045U42WH	85.65	30.00	42.00	45	78.75	39.00	H1SP45U42BK	H1SP45U42WH
H13145U42BK	H13145U42WH	85.65	31.50	42.00	45	78.75	39.00	H1SP45U42BK	H1SP45U42WH
H12445U48BK	H12445U48WH	85.65	24.00	48.00	45	78.75	45.00	H1SP45U48BK	H1SP45U48WH
H13045U48BK	H13045U48WH	85.65	30.00	48.00	45	78.75	45.00	H1SP45U48BK	H1SP45U48WH
H13145U48BK	H13145U48WH	85.65	31.50	48.00	45	78.75	45.00	H1SP45U48BK	H1SP45U48WH
H12448U42BK	H12448U42WH	90.87	24.00	42.00	48	84.00	39.00	H1SP48U42BK	H1SP48U42WH
H13048U42BK	H13048U42WH	90.87	30.00	42.00	48	84.00	39.00	H1SP48U42BK	H1SP48U42WH
H13148U42BK	H13148U42WH	90.87	31.50	42.00	48	84.00	39.00	H1SP48U42BK	H1SP48U42WH
H12448U48BK	H12448U48WH	90.87	24.00	48.00	48	84.00	45.00	H1SP48U48BK	H1SP48U48WH
H13048U48BK	H13048U48WH	90.87	30.00	48.00	48	84.00	45.00	H1SP48U48BK	H1SP48U48WH
H13148U48BK	H13148U48WH	90.87	31.50	48.00	48	84.00	45.00	H1SP48U48BK	H1SP48U48WH
H12452U42BK	H12452U42WH	97.90	24.00	42.00	52	91.00	39.00	H1SP52U42BK	H1SP52U42WH
H13052U42BK	H13052U42WH	97.90	30.00	42.00	52	91.00	39.00	H1SP52U42BK	H1SP52U42WH
H13152U42BK	H13152U42WH	97.90	31.50	42.00	52	91.00	39.00	H1SP52U42BK	H1SP52U42WH
H12452U48BK	H12452U48WH	97.90	24.00	48.00	52	91.00	45.00	H1SP52U48BK	H1SP52U48WH
H13052U48BK	H13052U48WH	97.90	30.00	48.00	52	91.00	45.00	H1SP52U48BK	H1SP52U48WH
H13152U48BK	H13152U48WH	97.90	31.50	48.00	52	91.00	45.00	H1SP52U48BK	H1SP52U48WH

Includes Frame, Two pair of square hole rails, vented front door, vented split rear door, 1x solid top and 1x brushed top.

H1 Top Panel Options

Part No. Black	Part No. White	Use with Cabinet Width	Description	Suggested Accessories
H1TS24BK	H1TS24WH	24	Solid	
H1TS30BK	H1TS30WH	30, 31.5	Solid	
H1TB24BK	H1TB24WH	24	Brushed side cable entry with center knockouts	
H1TB30BK	H1TB30WH	30, 31.5	Brushed side cable entry with center knockouts	
H1TC24BK	H1TC24WH	24	Thermal air chimney / Fan Top (fits any C2T1923**)	C2T1923F4TBK1
H1TC30BK	H1TC30WH	30, 31.5	Thermal air chimney / Fan Top (fits any C2T1923**)	C2T1923F4TLG1
H1TR24BK	H1TR24WH	24	9U Rack accessory mounting	
H1TR30BK	H1TR30WH	30, 31.5	9U Rack accessory mounting	

H1 Bottom Panel Options

Part No. Black	Part No. White	Descriptions	Use with Cabinet Width	Use with Cabinet Depth
H1BS2442BK	H1BS2442WH	Solid with cable entry knockouts	24	42
H1BS2448BK	H1BS2448WH	Solid with cable entry knockouts	24	48
H1BS3042BK	H1BS3042WH	Solid with cable entry knockouts	30, 31.5	42
H1BS3048BK	H1BS3048WH	Solid with cable entry knockouts	30, 31.5	48

H1 Vertical Ring and Finger Managers

Compatible with H1 Cabinet Height	Vertical Ring Manager	24" Width Includes one (1) Finger Vertical without a Cover	30" Width Includes two (2) Finger Verticals with Cover	31.5" Width Includes two (2) Finger Verticals with Cover
42U	H1VRM42UBK	H1VFM42UBK	H1VFMC3042UBK	H1VFMC3142UBK
45U	H1VRM45UBK	H1VFM45UBK	H1VFMC3045UBK	H1VFMC3145UBK
48U	H1VRM48UBK	H1VFM48UBK	H1VFMC3048UBK	H1VFMC3148UBK
52U	H1VRM52UBK	H1VFM52UBK	H1VFMC3052UBK	H1VFMC3152UBK

Air Dam Kit

Compatible with H1 Cabinet Height	24" Width	30" Width	31.5" Width
42U	H1AD2442BK	H1AD3042BK	H1AD3042BK
45U	H1AD2445BK	H1AD3045BK	H1AD3045BK
48U	H1AD2448BK	H1AD3048BK	H1AD3048BK
52U	H1AD2452BK	H1AD3052BK	H1AD3052BK

PDU Tray

Part No. Black Finish	Part No. White Finish	Compatible with H1 Cabinet Height
H1PDU42UBK	H1PDU42UWH	42U
H1PDU45UBK	H1PDU45UWH	45U
H1PDU48UBK	H1PDU48UWH	48U
H1PDU52UBK	H1PDU52UWH	52U

Tags: Server Rack Enclosure Cabinet, Rack Enclosure, Network Shelter, Net Shelter

Data subject to change without notice

© 2018. Hammond Manufacturing Ltd. All rights reserved.

